

COILED TUBING for Oil and Gas

**Quote Indiana Tube against your coiled tubing supplier.
We'll win you over on quality, lead time and value.**

Why endure the costly delays of CT mills that string you along for months? Indiana Tube has the standard sizes of small diameter, A606 carbon steel tubing you need — for well intervention, completion and velocity strings — in-stock and ready to ship.

- ITC-70 grade with tensile of 70,000 PSI yield strength and 80,000 PSI tensile strength
- ITC-80 grade with tensile of 80,000 PSI yield strength and 90,000 PSI tensile strength
- Coiled Tubing (CT) sizes: 0.750" (19.05 mm) to 1.5" (38.1 mm)
- Wall thicknesses ranging from 0.087" (1.65 mm) to 0.109" (2.77 mm)
- Shipped on steel reels or wood spools up to 20,000 lbs.



A HANDY & HARMAN COMPANY

2100 Lexington Avenue
Evansville, IN 47720
Phone: (812) 424-9028
Fax: (812) 424-0340
Email: indianatube@indianatube.com

www.IndianaTube.com

In-stock spooled tubing sizes

Outside Diameter		Wall Thickness	
		0.095"	0.109"
Inches	Metric	2.41 mm	2.77 mm
0.0750"	19.05 mm		
1.0000"	25.40 mm		
1.2500"	31.75 mm		
1.5000"	38.10 mm		

 Size range capability

Plus a wide selection of in-stock coiled and cut-to-length tubing sizes and build-to-order products.

Indiana Tube checks all your boxes:



High Quality

Industry grade with in-process weld integrity monitoring and data collection, electronic and eddy current monitoring, full body annealing, pressure and fatigue testing.



Faster Lead Times

Most sizes are available in-stock for delivery to your site in 4 weeks or less.



Best Value

We meet or beat the competition!